

TECHNICAL DATASHEET

SUPER GRADE 5W40



Fully synthetic motor oil for gasoline and diesel engines, with or without turbo

BO Super Grade is a fully synthetic motor oil for gasoline and diesel engines in passenger cars and light-duty commercial vehicles. This oil can be applied for cars equipped with catalytic converters, turbo-charged engines and for direct fuel injection systems.

BO Super Grade provides an extremely quick and stable lubricant film at the cold start and offers high thermal stability under heavy-duty operating conditions.

SPECIFICATION

Super Grade 5W40;
 API SN/CF
 ACEA A3/B3/B4 C2/C3-10
 VW 502.00/505.00/505.01
 MB 226.5/229.31
 BMW LL-04
 Porsche A40
 GM-LL-B-025/DEXOS 2
 Renault RN0700/RN0710
 PSA B712296
 Ford WSS-M2C934-B
 Super Grade 5W50/5W20

VALUE ANALYSIS

		5W40	ASTM
Soortelijk gewicht bij 20C	Kg/L	0,855	D4052
Viscositeit 100C	cSt	14,1	D445
Viscositeit 40C	cSt	87,0	D445
Viscositeit -30C	cP	<6600	D5293
Viscositeits Index		167	D2270
Vlampunt COC	C	222	D92
Stolpunt	C	-39	D6892
Sulfaatas	Gew%	1,19	D874
B.N. (HClO4-method)	mg/KOH/g	9,6	D2896

AVAILABLE PACKAGING

601030 - 1L, 601031 - 5L, 601032 - 20L, 601033 - 60L, 601034 - 210L

The contents of this document is intended to enable the reader to orient themselves on properties and potential applications of BO Motor Oil products. The information in this document at any time and without notice be altered because of continuous product research and development. The analytical data are listed in this product data sheet are typical values. Minor deviations, which may occur during the normal manufacturing process of the product, the quality of the product does not affect. Although this text has been compiled with great care, the compiler accepts no liability for damage caused by incompleteness and / or inaccuracies in the text. The reader is advised to make the final product in consultation with the supplier.